

**TECHNICAL DATA SHEET**

**1215HV**

**REPOSITIONABLE ADHESIVE**

---

**PRODUCT DESCRIPTION:**

**TYPICAL PROPERTIES:**

Viscosity 2/20/75°F: 450-650cP

Total Solids: 37-39%

Color: White

Application: Low Tack Repositionable Adhesive

**HANDLING & STORAGE:**

For best results, use product within 6 months.

**ROTATE STOCK:**

For best results, use older lots first.

**TOXICITY:**

Under normal conditions of use this product is considered nontoxic. Consult the MSDS for additional information.

**CLEAN UP:**

For best results, allow product to dry and remove manually with scraper or damp rag. Cleanup can be facilitated with the use of soapy hot water or a environmentally safe solvent. Contact your IN-LINE Finishing Solutions representative for additional assistance.

**FDA STATUS:**

Consult your IN-LINE Finishing Solutions representative for the most recent FDA status information.

**DISCLAIMER:**

The information given above is based on our best knowledge, and is believed to be true and accurate. No guaranty of accuracy is made. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions, and to determine whether the product is suitable for their purposes. Please read the entire product bulletin along with our conditions of sale, which apply to all goods supplied by us. IN-LINE Finishing Solutions assumes no responsibility for the use of these statements, recommendations or suggestions, nor do we intend them as a recommendation for any use which would infringe upon any patent or copyright.

*NOTE: The above specifications are tentative and subject to change based on actual batch history.*

---

**In-Line Finishing Solutions**  
**1000 N. Lake Shore Plaza, Unit 53A**  
**Chicago, IL 60611**