

Henkel Corporation  
 710 Ohio Street  
 Buffalo, NY 14240  
 Contact Information:  
 Telephone: 800-888-4910  
 Emergency Telephone: 860-571-5100

H.M.I.S.  
 HEALTH 1  
 FLAMMABILITY 0  
 REACTIVITY 0  
 These ratings should be used only  
 as part of full implemented  
 H.M.I.S. program.

**M A T E R I A L S A F E T Y D A T A S H E E T**

**SECTION 1 - PRODUCT INFORMATION**

DATE OF PREPARATION 9/19/05

TRADE NAME..... **PRIMAFIX POCKET ADHESIVE**      PHYSICAL FORM: **WATER**  
 MANUFACTURER CODE I.D. **26-17-3**      (Formerly a Sovereign Specialty Chemical Inc Product)

**SECTION 2 - HAZARDOUS INGREDIENTS/COMPOSITION INFORMATION**

INGREDIENT	% BY WGT	CAS NO.	ALLOWABLE EXPOSURE LEVEL	SARA 313	VP mm Hg @ 20 DEG.C	SKIN	
						PPM	MG/CU.M.
VINYL ACETATE	< 1	108-05-4	TLV-TWA				
			TLV-STEL	10	30		X
			OSHA-PEL	20	60		
			OSHA-STEL	10	30	C	
			LFL	20	60		
			UFL	3.0	13.0		

LFL = LOWER FLAMMABILITY LIMIT PERCENT  
 UFL = UPPER FLAMMABILITY LIMIT PERCENT  
 SKIN = SKIN ABSORPTION MUST BE CONSIDERED AS A ROUTE OF EXPOSURE  
 C-CEILING= ALLOW. EXPOSURE LEVEL SHOULD NOT BE EXCEEDED FOR ANY TIME PERIOD  
 MFR = MANUFACTURER RECOMMENDED EXPOSURE LIMIT  
 STEL = SHORT TERM EXPOSURE LIMIT  
 X-SARA 313 = CHEMICAL IS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313  
 OF TITLE III OF S.A.R.A. 40 CFR PART 372

**SECTION 3 - HAZARDS IDENTIFICATION**

EFFECTS OF SHORT TERM OVEREXPOSURE  
 SWALLOWING  
 Unknown  
 INHALATION  
 May cause respiratory irritation.  
 EYE  
 May cause eye irritation.  
 SKIN  
 May cause transient skin irritation.  
 EFFECTS OF REPEATED OVEREXPOSURE  
 None currently known  
 SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH.  
 The vinyl acetate supplier reports that there is limited evidence of  
 carcinogenicity of the monomer in animals (IARC Group 2B).

**SECTION 4 - FIRST-AID MEASURES**

SWALLOWING  
 If swallowed call Poison Control Center, Hospital Emergency Room, or

#### SECTION 4 - FIRST-AID MEASURES (Continued)

##### SWALLOWING

Physician immediately.

##### INHALATION

Remove to fresh air. Get medical attention.

##### EYE

Flush with large amounts of water, lifting upper and lower lids occasionally. Continue for at least 15 minutes. Get medical attention.

##### SKIN

Remove contaminated clothing. Wash affected area with soap and water. Obtain medical attention if irritation persists.

##### NOTES TO PHYSICIAN

Any treatment that might be required for overexposure should be directed at the control of symptoms and the clinical conditions.

#### SECTION 5 - FIRE-FIGHTING MEASURES

NFPA FLAMMABILITY CLASSIFICATION Not Applicable

FLASHPOINT Not applicable

EXTINGUISHING MEDIA

Will not burn.

UNUSUAL FIRE AND EXPLOSION HAZARDS

None known.

SPECIAL FIRE FIGHTING PROCEDURES

None known

#### SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Confine in small area; use absorbent to clean up. Place in container for disposal.

WASTE DISPOSAL

Dispose in accordance with federal, state and local regulations.

ENVIRONMENTAL HAZARDS

None known

#### SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Protect from freezing.

OTHER PRECAUTIONS

Do not take internally. Close container after each use. Keep away from children.

#### SECTION 8 - EXPOSURE CONTROLS

RESPIRATORY PROTECTION

Proper selection of respiratory protection depends upon many factors including duration and level of exposure and conditions of use. In general exposure to organic chemicals such as those contained in this product may not require the use of respiratory protection if used in well ventilated areas. In areas of restricted ventilation a NIOSH approved organic vapor respirator may be required. Under certain conditions, such as spraying, a mechanical prefilter may also be required. In confined areas or in high exposure situations a NIOSH/MSHA approved air supplied respirator may be required. If the TLV's or PEL's listed in Section II are exceeded use a properly fitted NIOSH/MSHA approved respirator with an appropriate protection factor. Refer to OSHA 29 CFR 1910.134 "Respiratory Protection", and "Respiratory Protection a Manual and Guideline, American Industrial Hygiene Association".

VENTILATION

Natural ventilation should be adequate under normal conditions.

**SECTION 8 - EXPOSURE CONTROLS (Continued)**

**HAND PROTECTION**

Not likely to be needed.

**EYE PROTECTION**

Wear safety spectacles with side shields. Wear face shield as necessary when spraying.

**OTHER PROTECTIVE EQUIPMENT**

Not likely to be needed.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

**BOILING RANGE** 212 DEG.F. ( 100 DEG.C.)

**VAPOR DENSITY** Heavier than air.    **% VOLATILE BY VOLUME** 68

**EVAPORATION RATE**            **VOC** .08 lb/gal less water& NPRS\*    10 g/l less water            CALCULATED  
Slower than diethyl ether.

**WEIGHT LB./GAL.** 9.9    **VOC** .13 lb/gal solids            16 g/l solids            CALCULATED  
**SPECIFIC GRAVITY** 1.2

All Physical data determined at 68 DEG. F. (20 DEG. C.) 760 mm Hg  
\* Negligibly Photochemically Reactive Materials

**SECTION 10 - STABILITY AND REACTIVITY**

**STABILITY**

Normally stable.

**CONDITIONS TO AVOID**

None known

**INCOMPATIBILITY (MATERIALS TO AVOID)**

None known

**HAZARDOUS DECOMPOSITION PRODUCTS**

Burning, including when heated by welding or cutting, will produce smoke, carbon monoxide and carbon dioxide.

**HAZARDOUS POLYMERIZATION**

Will not occur

**CONDITIONS TO AVOID**

None known

**SECTION 11 - TOXICOLOGICAL INFORMATION**

No information available.

**SECTION 12 - ECOLOGICAL INFORMATION**

No information available.

**SECTION 13 - DISPOSAL CONSIDERATIONS**

See Section 6.

**SECTION 14 - TRANSPORT INFORMATION**

<b>ITEM:</b>	26-17-3	<b>DESC/SIZE:</b> PRIMAFIX POCKET ADHESIVE
<b>MODE</b>	<b>PROPER SHIPPING NAME</b>	<b>CLASS I.D.# PKG GRP</b>
IATA		
(AIR)	ADHESIVES, NOT REGULATED	
DOT (HM-181)		
(DOMESTIC SURFACE)	ADHESIVES, NOT REGULATED	

**SECTION 14 - TRANSPORT INFORMATION (Continued)**

**ITEM:** 26-17-3 **DESC/SIZE:** PRIMAFIX POCKET ADHESIVE

MODE PROPER SHIPPING NAME CLASS I.D.# PKG GRP  
IMDG CODE  
(OCEAN) ADHESIVES, NOT REGULATED

NOTE! The assignment of Proper Shipping Names is in part a function of the size of the product container and the transport mode. For example, the Proper Shipping Name for a bulk container can differ significantly from the Proper Shipping Name for the same product packaged in a non-bulk container. This can also be true for products shipped via different modes of transportation (i.e. ground, air, ocean). The descriptions provided above are intended to provide some guidance. However, these descriptions may not apply to your package size or mode of shipment. The U.S. Code of Federal Regulations, 49 CFR - Transportation, regulations, and the policies established by some transporters, require that the shipper properly classify and assign a Proper Shipping Name, and label, mark and package the material properly. Therefore, the user of this information is cautioned to consult with applicable regulations, and with qualified advisors prior to the repackaging and or reshipment of this or other any product which contain this product.

**SECTION 15 - REGULATORY INFORMATION**

All ingredients in this product are listed on the US TSCA Inventory.

INGREDIENT	CAS NO.	DETAIL INVENTORY LIST INFORMATION
VINYL ACETATE	108-05-4	TSCA(8d) DSL

DETAIL INVENTORY LIST DESCRIPTION

TSCA/Toxic Substances Control Act  
(8d)Health and Safety Reporting Rules  
DSL/Canadian Domestic Substance List

**SECTION 16 - OTHER INFORMATION**

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

-----  
For Safety and Regulatory Information contact:  
Product Safety and Regulatory Affairs,  
Rocky Hill, CT  
860-571-5204