



# Adhesin® 2742

Remoistenable Adhesive

January 2010

Formerly known as Adhesin® A 32-74-2

## TYPE OF ADHESIVE:

Remoistenable Adhesive

## FIELD OF APPLICATION:

Graphic Arts > Direct Mail > Remoistenable

## TYPICAL TECHNICAL DATA :

Viscosity: 1100 cPs at 76°F Brookfield

pH: 5.5

Density: 9.0 lbs/gallon

Color: White Liquid

Solids: 50%

## PROPERTIES:

Adhesin® 2742 is a high solids remoistenable adhesive for web presses. Adhesin® 2742 has excellent adhesion to coated paper. It has excellent machining and layflat properties and is easy to clean up. Specifically designed to be fast drying. All ingredients in Adhesin® 2742 are approved under the Federal Regulation 21 CFR 175.105, which relates to incidental contact of adhesives with food.

## HANDLING AND APPLICATION :

Adhesin® 2742 is supplied ready for use. The recommended adhesive spread is 1 wet mil or 0.5 dry mil. Preferred running temperature is 70-85°F. This adhesive cleans up with water while wet or dry.

## PRECAUTIONS:

Do not mix with other adhesives. Please refer to the Material Safety Data Sheet for further information.

## STORAGE CONDITIONS:

Adhesin® 2742 has a 90 day shelf life. Rotate stock, using oldest first. Keep container covered when not in use to prevent moisture loss and contamination. Do not freeze.

## Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

## Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

1/2010csw